## AIR TURQUOISE SA | PARA-TEST.COM

Route du Pré-au-Comte 8 🔺 CH-1844 Villeneuve 🔺 +41 (0)21 965 65 65

Test laboratory for paragliders, paraglider harnesses and paraglider reserve parachutes



## Flight test report: EN 926-2:2013 & LTF 91/09

g toot .op	0101 211 020 2120 10				
Manufacturer	ParAAvis Co.	Certification number	F	PG_1752.2020	
Address	17A/2 st.Iskry 129344 Moscow Russia	Flight test	0	5.01.2021	
Glider model	Cab 42	Classification	Е	3	
Serial number	5420	Representative		lone	
		•			
Trimmer	yes: opened	Place of test	V	/illeneuve	
Folding lines used	no				
Test pilot		Alain Zoller	C	Claude Thurnheer	
Harness		Advance - Success 4 L	Δ	Advance - Bi pro 2	
	istance (cm)	44		55	
Harness to risers distance (cm)			_		
Distance between r	` '	48		55	
Total weight in fligh	nt (kg)	120	2	220	
1. Inflation/Take-off		В			
Rising behaviour		Easy rising, some pilot correction is required	В	Easy rising, some pilot correction is required	В
Special take off technique	required	No	Α	No	Α
2. Landing		Α			
Special landing technique	required	No	Α	No	Α
3. Speed in straight fligh		В			
Trim speed more than 30 km/h		Yes	Α	Yes	Α
Speed range using the controls larger than 10 km/h		Yes	Α	Yes	Α
Minimum speed		Less than 25 km/h	Α	25 km/h to 30 km/h	В
4. Control movement		Α			
Max. weight in flight up					
Symmetric control pressure / travel		not available	0	not available	0
Max. weight in flight 80 kg to 100 kg					
Symmetric control pressure / travel		not available	0	not available	0
Max. weight in flight gre	<u> </u>				
Symmetric control pressur		Increasing / greater than 65 cm	Α	Increasing / greater than 65 cm	Α
5. Pitch stability exiting accelerated flight			^		0
Dive forward angle on exit		not available	0	not available	0
Collapse occurs  6. Pitch stability operation flight	ng controls during accelerated	not available 0	U	not available	U
Collapse occurs		not available	0	not available	0
7. Roll stability and dam	ping	Α			
Oscillations		Reducing	Α	Reducing	Α
8. Stability in gentle spir	rals	A		<u> </u>	
Tendency to return to stra		Spontaneous exit	Α	Spontaneous exit	Α
9. Behaviour exiting a fu	Illy developed spiral dive	В			
Initial response of glider (f	first 180°)	Immediate reduction of rate of turn	Α	No immediate reaction	В
Tendency to return to stra	ight flight	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α	Spontaneous exit (g force decreasing, rate of turn decreasing)	Α
Turn angle to recover nor	mal flight	Less than 720°, spontaneous recovery	Α	720° to 1 080°, spontaneous recovery	В
10. Symmetric front coll	apse	Α			
Approximately 30 % cho	ord				
Entry		Rocking back less than 45°	Α	Rocking back less than 45°	Α

Description	0		0	
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit Change of course	Dive forward 0° to 30° Keeping course	Α	Dive forward 0° to 30° Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No		No	
At least 50% chord				
	Rocking back less than 45°	Α	Rocking back less than 45°	Α
Entry	· ·		•	
Recovery	Spontaneous in less than 3 s	Α.	Spontaneous in less than 3 s	A
Dive forward angle on exit / Change of course	Dive forward 0° to 30° / Keeping course	Α	Dive forward 0° to 30° / Keeping course	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No		No	
With accelerator				
Entry	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit / Change of course	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available		Not available	
11. Exiting deep stall (parachutal stall)	A			
Deep stall achieved	Yes	Α	Yes	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Change of course	Changing course less than 45°	A	Changing course less than 45°	A
Cascade occurs	No	Α	No	Α
12. High angle of attack recovery	<b>A</b>			
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Cascade occurs	No	Α	No	Α
13. Recovery from a developed full stall	A			
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
Collapse	No collapse	Α	No collapse	Α
Cascade occurs (other than collapses)	No	Α	No	Α
Rocking back	Less than 45°	Α	Less than 45°	Α
Line tension	Most lines tight	Α	Most lines tight	Α
14. Asymmetric collapse	В			
Small asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	Less than 90° / Dive or roll angle 15° to 45°	Α
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of	Α	No (or only a small number of	Α
	collapsed cells with a spontaneous reinflation)		collapsed cells with a spontaneous reinflation)	
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No		No	
Large asymmetric collapse				
Change of course until re-inflation / Maximum dive forward or roll angle	90° to 180° / Dive or roll angle 15° to 45°	В	90° to 180° / Dive or roll angle 15° to 45°	В
Re-inflation behaviour	Spontaneous re-inflation	Α	Spontaneous re-inflation	Α
Total change of course	Less than 360°	Α	Less than 360°	Α
Collapse on the opposite side occurs	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α	No (or only a small number of collapsed cells with a spontaneous reinflation)	Α
Twist occurs	No	Α	No	Α
Cascade occurs	No	Α	No	Α
Folding lines used	No		No	
Small asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0

Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available		Not available	
Large asymmetric collapse with fully activated accelerator				
Change of course until re-inflation / Maximum dive forward or roll angle	not available	0	not available	0
Re-inflation behaviour	not available	0	not available	0
Total change of course	not available	0	not available	0
Collapse on the opposite side occurs	not available	0	not available	0
Twist occurs	not available	0	not available	0
Cascade occurs	not available	0	not available	0
Folding lines used	Not available		Not available	
15. Directional control with a maintained asymmetric	A			
collapse				
Able to keep course	Yes	Α	Yes	Α
180° turn away from the collapsed side possible in 10 s	Yes	Α	Yes	Α
Amount of control range between turn and stall or spin	More than 50 % of the symmetric control travel	Α	More than 50 % of the symmetric control travel	Α
16. Trim speed spin tendency	Α			
Spin occurs	No	Α	No	Α
17. Low speed spin tendency	Α			
Spin occurs	No	Α	No	Α
18. Recovery from a developed spin	Α			
Spin rotation angle after release	Stops spinning in less than 90°	Α	Stops spinning in less than 90°	Α
Cascade occurs	No	Α	No	Α
19. B-line stall	A			
Change of course before release	Changing course less than 45°	Α	Changing course less than 45°	Α
Behaviour before release	Remains stable with straight span	Α	Remains stable with straight span	Α
Recovery	Spontaneous in less than 3 s	Α	Spontaneous in less than 3 s	Α
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 30° to 60°	Α
Cascade occurs	No	Α	No	Α
20. Big ears	В			
Entry procedure	Dedicated controls	Α	Dedicated controls	Α
Behaviour during big ears	Stable flight	Α	Stable flight	Α
Recovery	Recovery through pilot action in less than a further 3 s	В	Recovery through pilot action in less than a further 3 s	В
Dive forward angle on exit	Dive forward 0° to 30°	Α	Dive forward 0° to 30°	Α
21. Big ears in accelerated flight	0			
Entry procedure	not available	0	not available	0
Behaviour during big ears	not available	0	not available	0
Recovery	not available	0	not available	0
Dive forward angle on exit	not available	0	not available	0
Behaviour immediately after releasing the accelerator while maintaining big ears	not available	0	not available	0
22. Alternative means of directional control	A			
180° turn achievable in 20 s	Yes	Α	Yes	Α
Stall or spin occurs	No	Α	No	Α
23. Any other flight procedure and/or configuration described in the user's manual	0			
Procedure works as described	not available	0	not available	0
Procedure suitable for novice pilots	not available	0	not available	0
Cascade occurs	not available	0	not available	0

24. Comments of test pilot